



THROTTLE POSITION RELEARN INSTRUCTIONS

CHRYSLER / DODGE / JEEP

STEP-BY-STEP INSTRUCTIONS

1. Turn the Ignition Key to the “ON” Position

Donot start the engine. Just turn the key to the “ON” position so that the dashboard lights turn on.



2. Wait for 10 Seconds

Allow he throttle body to initialize. You may hear a slight humming or clicking sound — this is normal.



3. Press the Accelerator Pedal Slowly

Press th pedal slowly all the way to the floor, then slowly release it back to its resting position.



4. Power Down the Ignition

Turn the ignition to the OFF position and allow the system to remain off for at least 10 seconds.



5. Start the Engine

Start the engine and let it idle for a few minutes without pressing the accelerator. Idle speed may fluctuate — this is part of the ECM relearning the throttle position.



6. Test Drive

Take the vehicle for a short test drive to confirm that throttle response is smooth and consistent.



ADDITIONAL STEPS (IF REQUIRED)

- If this manual procedure does not work, a scan tool with throttle relearn capability may berequired.
- If the vehicle continues to have issues after the relearn, check for:
 - Stored trouble codes
 - Throttle body faults
 - Wiring or connection issues

SCAN



Still having issues?

Visit:

<https://www.automotivediscounts.com/tools/technical-assistance-ticket>
and **open a Technical Support Ticket.**

